



Micro Commercial Components

Micro Commercial Components  
20736 Marilla Street Chatsworth  
CA 91311  
Phone: (818) 701-4933  
Fax: (818) 701-4939

# MCQ4559

## Features

- Halogen free available upon request by adding suffix "-HF"
- Lead Free Finish/Rohs Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Marking: Q4559

## N and P-Channel Enhancement Mode Field Effect Transistor


### Maximum ratings ( $T_a=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	N-Channel	P-Channel	Unit
Drain-Source Voltage	$V_{DS}$	60	-60	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	$\pm 20$	V
Continuous Drain Current <sup>(note1)</sup>	$I_D$	4.5	-3.5	A
Pulsed Drain Current	$I_{DM}$	18	-14	A
Continuous Source-Drain Diode Current	$I_S$	4.5	-3.5	A
Power Dissipation	$P_D$	2.0		W
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	62.5		$^{\circ}\text{C/W}$
Operating Junction Temperature	$T_J$	150		$^{\circ}\text{C}$
Storage Temperature	$T_{STG}$	-55 ~ +150		


### Notes :

1. Surface mounted on FR4 board using the minimum recommended pad size.
2. Pulse Test : Pulse width=300 $\mu\text{s}$ , duty cycle $\leq 2\%$ .
3. Switching characteristics are independent of operating junction temperature.
4. Guaranteed by design, not subject to producing.

### Equivalent Circuit



## SOP-8



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.053	0.069	1.350	1.750	
B	0.004	0.010	0.100	0.250	
C	0.053	0.061	1.350	1.550	
D	0.013	0.020	0.330	0.510	
E	0.007	0.010	0.170	0.250	
F	0.189	0.197	4.800	5.000	
G	0.050 (BSC)		1.270 (BSC)		
H	0.228	0.244	5.800	6.200	
J	0.150	0.157	3.800	4.000	
K	0.016	0.050	0.400	1.270	
$\theta$	0 $^{\circ}$	8 $^{\circ}$	0 $^{\circ}$	8 $^{\circ}$	

## MOSFET ELECTRICAL CHARACTERISTICS

### N-ch MOSFET ELECTRICAL CHARACTERISTICS( $T_a=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
<b>STATIC CHARACTERISTICS</b>						
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	60			V
Zero gate voltage drain current	$I_{DSS}$	$V_{DS} = 60V, V_{GS} = 0V$			1	$\mu A$
Gate-body leakage current	$I_{GSS}$	$V_{GS} = \pm 20V, V_{DS} = 0V$			$\pm 100$	nA
Gate threshold voltage (note 2)	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	1	2.1	3	V
Drain-source on-resistance(note 2)	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 4.3A$		40	58	m $\Omega$
		$V_{GS} = 4.5V, I_D = 3.9A$		55	72	m $\Omega$
Forward tranconductance(note 2)	$g_{FS}$	$V_{DS} = 15V, I_D = 4.3A$		15		S
Diode forward voltage	$V_{SD}$	$I_S = 1.7A, V_{GS} = 0V$			1.2	V
<b>DYNAMIC CHARACTERISTICS (note 4)</b>						
Input Capacitance	$C_{iss}$	$V_{DS} = 15V, V_{GS} = 0V, f = 1MHz$		665		pF
Output Capacitance	$C_{oss}$			75		pF
Reverse Transfer Capacitance	$C_{rss}$			40		pF
Gate Resistance	$R_g$	$f = 1MHz$			3	$\Omega$
<b>SWITCHING CHARACTERISTICS (note 3,4)</b>						
Turn-on delay time	$t_{d(on)}$	$V_{GEN} = 4.5V, V_{DD} = 30V, I_D = 3.4A, R_G = 1\Omega, R_L = 8.8\Omega$			25	ns
Turn-on rise time	$t_r$				100	ns
Turn-off delay time	$t_{d(off)}$				25	ns
Turn-off fall time	$t_f$				15	ns
Total Gate Charge	$Q_g$	$V_{DS} = 30V, I_D = 4.3A, V_{GS} = 4.5V$			9	nC
Gate-Source Charge	$Q_{gs}$			2.3		nC
Gate-Drain Charge	$Q_{gd}$			2.6		nC


### P-ch MOSFET ELECTRICAL CHARACTERISTICS( $T_a=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
<b>STATIC CHARACTERISTICS</b>						
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = -250\mu A$	-60			V
Zero gate voltage drain current	$I_{DSS}$	$V_{DS} = -60V, V_{GS} = 0V$			-1	$\mu A$
Gate-body leakage current	$I_{GSS}$	$V_{GS} = \pm 20V, V_{DS} = 0V$			$\pm 100$	nA
Gate threshold voltage (note 2)	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = -250\mu A$	-1	-2.8	-3	V
Drain-source on-resistance(note 2)	$R_{DS(on)}$	$V_{GS} = -10V, I_D = -3.1A$		60	80	m $\Omega$
		$V_{GS} = -4.5V, I_D = -0.2A$		92	100	m $\Omega$
Forward tranconductance(note 2)	$g_{FS}$	$V_{DS} = -15V, I_D = -3.1A$		8.5		S
Diode forward voltage	$V_{SD}$	$I_S = -2A, V_{GS} = 0V$			-1.2	V
<b>DYNAMIC CHARACTERISTICS (note 4)</b>						
Input Capacitance	$C_{iss}$	$V_{DS} = -15V, V_{GS} = 0V, f = 1MHz$		650		pF
Output Capacitance	$C_{oss}$			95		pF
Reverse Transfer Capacitance	$C_{rss}$			60		pF
Gate Resistance	$R_g$	$f = 1MHz$			20	$\Omega$
<b>SWITCHING CHARACTERISTICS (note 3,4)</b>						
Turn-on delay time	$t_{d(on)}$	$V_{GEN} = -4.5V, V_{DD} = -30V, I_D = -2.4A, R_G = 1\Omega, R_L = 12.5\Omega$			45	ns
Turn-on rise time	$t_r$				105	ns
Turn-off delay time	$t_{d(off)}$				60	ns
Turn-off fall time	$t_f$				45	ns
Total Gate Charge	$Q_g$	$V_{DS} = -30V, I_D = -3.1A, V_{GS} = -4.5V$			12	nC
Gate-Source Charge	$Q_{gs}$			2.2		nC
Gate-Drain Charge	$Q_{gd}$			3.7		nC




# Typical Characteristics

## N-Channel MOS



**Output Characteristics**



**Transfer Characteristics**




**Threshold Voltage**







# Typical Characteristics

## P-Channel MOS


Output Characteristics



Transfer Characteristics



Threshold Voltage





Micro Commercial Components

### Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel:4Kpcs/Reel

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.