



LEAD FINISH: GOLD PL.	
CASING FINISH: GOLD PL.	
CAPACITANCE	25pF MIN.
TEMP. RANGE	-55°C TO 125°C
CURRENT	10 AMP MAX.
WORKING VOLTAGE	125°C -- VAC MAX. 125°C 200 VDC MAX.
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHz	I.L. (db)
1	--
10	--
100	--
1 GHz	13
10 GHz	25



NOTES:
1. SUGGESTED MOUNTING HOLE = Ø.130

MARKING:
PART: BLUE COLOR DOT
BAG:
SCI-9980-250
DATE CODE
LOT NO.
QTY/BAG (200 MAX.)

	00	REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED	 FAIRVIEW PENNSYLVANIA SPECTRUM CONTROL INC.	
	CN 53135-ENG	CHANGE NOTICE	Fractions ± 1/64		Dwn. KAUFFMAN
			Dec. .xx ±		Date 2-25-10
			Dec. .xxx ± .005		Engr. B. DEVINE
			Angles ± 0° 30'		Scale NONE
		CODE IDENT. NO. DLSP2	Description FEEDTHRU FILTER SCI-9980-250		