



IMPEDANCE (Z)			
Frequency	25 MHz	100 MHz	300 MHz
Nominal (REF)	75 Ω	192 Ω	380 Ω
Minimum	- Ω	154 Ω	- Ω




UNCONTROLLED DOCUMENT

FERRITE CORE DIMENSIONS (SPEC): mm [in]

A	28.00 [1.102]	±	0.51 [0.020]
B	23.00 [0.906]	±	0.35 [0.014]
C	20.00 [0.787]	±	0.40 [0.016]
D	5.80 [0.228]	-	0.25 [0.010]
E	0.80 [0.031]	-	0.25 [0.010]

WEIGHT/1000 13.98 kgs [30.82 Lbs]

NOTES: UNLESS OTHERWISE SPECIFIED
1. COSMETIC SPECIFICATION REFER TO WI-QA-038.



DIMENSIONS ARE IN mm[INCHES].				This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.		Laird	
D	UPDATE COMPANY LOGO	12/28/12	QIU	PROJECT/PART NUMBER:		REV	DRAWN BY:
C	UPDATE MIN Z SPEC & COMPANY LOGO	07/27/07	JRK	28R1102-100		D	JRK
B	UPDATE MIN Z SPEC @100Mhz, ADD REF #	01/27/04	JRK	DATE:	07/10/03	SCALE:	3 : 1
A	ORIGINAL DRAFT	07/10/03	JRK	CAD #	28R1102-100-D	TOOL #	R1102
REV	DESCRIPTION	DATE	INT			MATERIAL: FERRITE	